

MULTIPACK Ballenpresse

Datenblatt



EINKAMMERPRESSE

MP 500A, 500S,
MP 600A

MP 820

MP 836


MP 840, MP 850

TYP	Press- druck	Motor	Pressdauer inkl. Rückhub	Einfüll- höhe	Einfüll- öffnung	Presskasten B x T x H	Ballenformat	Ballen- gewicht
	kN	kW / V / Hz	sec.	mm	mm	mm	mm	kg
MP 500 A	50	1,5 / 400 / 50	20	1020	650 x 450	650 x 450 x 850	650 x 450 x 450	30 - 60
MP 500 S	50	1,5 / 400 / 50	20	1070	700 x 500	700 x 500 x 900	-	30 - 60
MP 600 A	60	1,5 / 400 / 50	25	1070	700 x 500	700 x 500 x 900	700 x 500 x 500	40 - 80
MP 820	160	4,0 / 400 / 50	24	850	1100 x 600	1100 x 700 x 1250	1100 x 700 x 800	100 - 220
MP 836	260	4,0 / 400 / 50	40	1100	1200 x 600	1200 x 800 x 1550	1200 x 800 x 800-1000	300 - 400
MP 840	300	5,5 / 400 / 50	35	1100	1090 x 570	1200 x 800 x 1550	1200 x 800 x 1000	300 - 400
MP 850	500	7,5 / 400 / 50	40	1100	1090 x 570	1200 x 800 x 1550	1200 x 800 x 1000	300 - 500

TYP	Empfohlene Tages- leistung	Maximale Ballen- leistung	Bindung vertikal	Bindeband	Bindedraht	Breite	Tiefe x Höhe	Gewicht	Absicherung träge
	Ballen / Tag	Ballen / Std.		mm	mm	mm	mm	kg	A
MP 500 A	5 - 10	2 - 3	2 v	9	-	920	1110 x 1880	345	12
MP 500 S	5 - 10	2 - 3	-	-	-	950	1170 x 1950	400	12
MP 600 A	5 - 10	2 - 3	2 v	9	-	970	1200 x 1950	400	12
MP 820	5 - 10	2 - 3	4 v	13	-	1580	930 x 1950	1140	16
MP 836	5 - 10	2 - 3	4 v	13	2,5	1640	1150 x 2500	1600	16
MP 840	5 - 10	2 - 3	4 v	16	2,5	1620	1250 x 2920	1695	16
MP 850	5 - 10	2 - 3	4 v	16	2,5	1620	1250 x 2920	2180	25



MP 500S/II
MP 700/II



MP 720/II

MEHRKAMMERPRESSE

TYP	Pressdruck	Motor	Pressdauer inkl. Rückhub	Einfüllhöhe	Einfüllöffnung	Presskasten B x T x H	Ballenformat	Ballengewicht
	kN	kW / V / Hz	sec.	mm	mm	mm	mm	kg
MP 500 S/II	50	1,5 / 400 / 50	20	1070	700 x 500	700 x 500 x 900	650 x 450 x 450	30 - 60
MP 700/II	60	1,5 / 400 / 50	25	1050	700 x 500	700 x 500 x 850	700 x 500 x 500	40 - 80
MP 720/II	200	4,0 / 400 / 50	24	1420	1100 x 700	1100 x 700 x 1150	1100 x 700 x 800	150 - 250

TYP	Empfohlene Tagesleistung	Maximale Ballenleistung	Bindung vertikal	Bindeband	Binde- draht	Breite	Tiefe x Höhe	Gewicht	Absicherung träge
	Ballen / Tag	Ballen / Std.		mm	mm	mm	mm	kg	A
MP 500 S/II	5 - 10	2 - 3	2 v	9	-	1760	850 x 2000	575	12
MP 700/II	5 - 10	2 - 3	2 v	9	-	1800	850 x 1970	616	12
MP 720/II	5 - 10	2 - 3	4 v	13	-	2520	1200 x 2500	1640	16



MP 620
Dosenpresse



MP 630/640
Fasspresse



MP 650
Containerpresse

SPEZIALPRESSE

TYP	Pressdruck	Motor	Gewicht	Außenmaße L x B x H	Max. Gebinde- durchmesser	Leistung
	kN	kW / V / Hz	kg	mm	mm	Stk./h
MP 620 A Dosenpresse	100	1,5 / 400 / 50	320	630 x 810 x 2150	400 x 620	50
MP 630 Fasspresse	200	4 / 400 / 50	770	1000 x 890 x 2450	700 x 950	60
MP 640 Fasspresse	270	5,5 od. 7,5 / 400 / 50	940 - 970	1000 x 940 x 2470	700 x 950	50/60
MP 650 Containerpresse	40	1,5 x 400 x 50	350	1540 x 1650 x 2370	-	-

